Problems and Exercises in Mathematical (Cont.)	SOV/2061	
Ploblems and		•
TABLE OF CONTENTS:		7
Preface		9
Ch. I. Introduction to Analysis  1. Concept of a function  2. Graphs of elementary functions  3. Limits  4. Infinitesimals and infinitely large values  5. Continuity of functions		9 14 20 31 34
Ch. II. Differentiation of Functions  1. Direct computation of derivatives  2. Table of differentiation formulas  3. Derivatives of functions not clearly defined  4. Geometric and mechanical applications of a d  5. Derivatives of higher orders  6. Differentials of the first and higher orders  7. Mean value theorems  8. Taylor's formula  9. Hospital-Bernoulli rule for evaluating indet		40 44 54 58 64 68 72 73
Card 3/10		

Proble	ms and Exercises in Mathematical (Cont.) SOV/2	ov/2061	
	I. Extrema of Functions and Geometric Applications of a Derivative	79	
Ch. 11	Extrema of a function of one argument		
		87	
2.	A A A A A A	89	
	Asymptotes Constructing the graphs of functions by characteristic points	91	
4.	Differential of an arc. Curvature	97	
5.	Differential of an arc. Convacuit		
A) 711	m. Talatinita Intogral	102	
Ch. IV	. The Indefinite Integral Direct integration	102	
2.	Method of substitutions	108	
3.	Integration by parts	111	
	Simplest integrals containing quadratic trinomials	113	
4.	Integration of rational functions	116	
5.		120	
6. 7.		123	
8.		128	
9.	A lighting of trigonometric and hyperbolic substitutions for com-	-	
9.	puting integrals of the form $\int R(x, \sqrt{ax^2 + bx + c}) dx$ , where		
	R is a rational function	129	
	R is a rational function		

Problems and Exercises in Mathematical (Cont.) SOV/206	1
	130
. 10. Integration of various transcendental functions	131
11. Application of "reduction formulas"	131
12. Miscellaneous examples of integration	
	133
Ch. V. The Definite Integral	133
1. The definite integral as the limit of a sum	135
<ol> <li>Ine definite integral as the lamb of indefinite integrals</li> <li>Computing definite integrals by means of indefinite integrals</li> </ol>	138
3. Improper integrals	141
4. Substitution of variable in a definite integral	144
5. Integration by parts	145
6. Mean value theorem	147
7. Areas of plane figures	153
8. Length of an arc of a curve	155
9. Volume of solids	160
10. Area of a surface of revolution	162
 <ol> <li>Moments. Centroids. Guldenus' theorems</li> <li>Applications of definite integrals to the solution of physical</li> </ol>	166
problems	
Card 5/10	
Card 3/10	

Ch. VI	. Functions of Several Variables	172
1.	Fundamental concepts	172
2.	Continuity	175
3.	Partial derivatives	177 179
4.		182
5.	Differentiation of composite functions	
6.		185
7.		188
8.		193 195
9.	Differentiation of implicit functions	202
10.	Substitution of variables	
11.	Tangential plane and normal to a surface	207
12.	Taylor's formula for a function of several variables	210
13.	Fytreme of a function of several variables	210
14.		216
15.		219
16.	Envelope	222
17.		
18.	Vector-function of a scalar argument	223
19.	The moving trihedral of a space curve	226
20.		230

roblems and Exercises in Mathematical (Cont.)	SOV/2061
h. VII. Multiple and Line Integrals  1. Double integrals in rectangular coordinates  2. Substitution of variables in a double integral  3. Calculating areas  4. Calculating volumes  5. Calculating the areas of surfaces	233 233 239 242 244 246 247
6. Applications of the double integral to mechanics 7. Triple integrals 8. Improper integrals depending on parameter. Improper multipl 9. Line integrals 10. Surface integrals 11. Ostrogradskiy-Gauss formula 12. Elements of field theory	248
Ch. VIII. Series  1. Numerical series 2. Series of functions 3. Taylor series 4. Fourier series Card 7/10	27 27 28 29 30

ı. IX	. Differential Equations	30
1.	Verifying solutions. Formation of differential equations of fami-	
	lies of curves. Initial conditions	30
2.	Differential equations of the first order	30
3.	Differential equations of the first order with separable variables.	
	Orthogonal trajectories	31
4.	Homogeneous differential equations of the first order	31
5.	Linear differential equations of the first order. Bernoulli	
	equations	31
6.	Exact differential equations. Integrating factor	31
7.	Differential equations of the first order not solved with respect	
	to the derivative	32
8.	Clairaut and Lagrange equations	32
9.	Miscellaneous exercises on differential equations of the first order	32
10.	Differential equations of higher orders	. 32
11.	Linear differential equations	33
12.	Linear differential equations of the second order with constant	
	coefficients	33
13.	Linear differential equations with constant coefficients of order	
	higher than second	34

	Euler's equations	. 34
15.	Systems of differential equations	34
16.	Integration of differential equations by means of power series	34
17.	Problems on Fourier's method	34
Ch. X.	Approximate Computations	35
1.	Operations on approximate numbers	35
2.	Integration of functions	35
3.	Computing the real roots of equations	35
4.	Numerical integration of functions	36 36
5. 6.	Numerical integration of ordinary differential equations Approximate computation of Fourier coefficients	37
0.	Approximate compatation of roditer coefficients	
Answers		37
		AL
Appendi	xes:	46
Appendi		
•	xes: ek Alphabet	46 46
I. Gre	ek Alphabet	
•	ek Alphabet	

Problems and Exercises in Mathematical (Cont.)  II. Certain Constants	SOV/2061
	460
III. Inverse Values, Powers, Roots, Logarithms	461
IV. Trigonometric Functions	
V. Exponential, Hyperbolic, and Trigonometric Functions	463
VI. Certain Curves	464
	465
AVAILABLE: Library of Congress	
Card 10/10	
	LK/1sb 8-26-59

BARANENKOV, G.S.; DEMIDOVICH, B.P.; YEFIMENKO, V.A.; KOGAN, S.M.; LUNTS, G.L.; PORSHNEVA, Ye.F.; SYCHEVA, Ye.P.; FROLOV, S.V.; SHOSTAK, R.Ya.; YANPOL'SKIY, A.R.; UGAROVA, N.A., red.; SMOLYANSKIY, M.L., red.; BRUDNO, K.F., tekhn. red.

[Problems and exercises in mathematical analysis for shools of higher education] Zadachi i uprachmeniia po matematicheskomu analizu dlia vtuzov. Izd.2., ispr. Moskva, Gos. izd-vo fizikomatem. lit-ry, 1961. 472 p.

(MIRA 14:8)

(Mathematical analysis—Problems, exercises, etc.)

BARANENKOV, G.S.; DEMIDOVICH, B.P.; YEFIMENKO, V.A.; KOGAN, S.M.;
LUNTS, G.L.; PORSHNEVA, Ye.F.; SYCHEVA, Ye.P.; FROLOV,
S.V.; SHOSTAK, R.Ya.; YANPOL'SKIY, A.R.; BAYEVA, A.P., red.;
BRUDNO, K.F., tekhn. red.

[Problems and exercises in mathematical analysis] Zadachi i uprazhneniia po matematicheskomu analizu dlia vtuzov. Pod red. B.P.Demidovicha. Izd.4., ispr. Moskva, Fitmazgiz, 1963 472 p.

(MIRA 16:10)

(Mathematical analysis—Problems, exercises, etc.)

YEFILENKO, V.F. (Vladivostok); YERKIN, A.M. (Barnaul)

What a new textbook on physics should be like. Fiz. v shkole (MIRA 16:12)

YEFIMENKO, V. I. Cand Shem Sci -- (diss) "Isomerizational conversions of certain terepene analysis hydrosarbons in the presence of resin acids." Minsk, 1959

17 pp with charts (Belorussian State Univ im V. I. Lenin), 150 copies

(KL, 52-59, 117)

-17-

#### BARDYSHEV, I.I.; YEFIMENEO, V.I.

Isomerization of terpenes in the presence of resin acids.

Isomerization transformations of 3-carene. Dokl. AN BSSR 3
no.4:150-153 Ap '59. (MIRA 12:10)

1. Predstavleno akademikom AN BSSR B.V. Yerofeyevym. (Carene) (Isomerization)

YEFIMENKO, V.I.

Results of introducing the method of sait-free settling of oleoresins. Gidroliz. i lesokhim. prom. 18 no.3:26-27 (65. (MIRA 18:5)

1. Klyevskiy khimicheskiy kombinat.

BARDYSHEV, I.I.; YEFIMENKO, V.I.

Isomerization conversions of terpenes in the presence of resin acids. Isomerization conversions of  $\beta$ -pinene. Sbor. nauch. rab. Inst. fiz.-org. khim. AN BSSR no. 7:188-191 '59.

(MIRA 14:4)

(Pinene)

BARDYSHEV, I.I.; YEFIMENKO, V.I.; ERILANE, A.F.; NAUMOVA, N.I.

eritein eritein australia eritein erit

Continuous esterification of rosin. Gidroliz. i lesokhim.prom.
17 no.2:20-21 '64. (MIRA 17:4)

1. Institut fizicheskoy i organicheskoy khimii AN Belorusskoy SSR (for Bardyshev). 2. Kiyevskiy lesokhimicheskiy kombinat (for Yefimenko, Erilane, Naumova).

ATAMANCHUKOV, G.D.; ERILANE, A.F.; YEFFERENEO, V.T.; NAURAVA, N.I.

Use of heat treated rosin for the production of the "Fly trag"

sticky subctance. Gidroliz ! losokhim. pron. 17 no.5:21-25 164.

(Mink 17:10)

1. TSentral'nyy nauchac-isaledovatel'skty losokhimionoskly institut
(for Atamanchukov). 2. Kiyevskiy losokhimioherkiy kombinat (for Erilane,
Yefimenko, Naumova).

YEFIMENKO, V. L.

YEFIMENKO, V. L.: "Aspects of vascular reflexes in various forms of hypertonic psychoses" (Clinical-physiological investigation). Leningrad, 1955.
Min Health RSFSR. Leningrad Sanitary-Hygienic Medical Inst. (Dissertation for the Degree of Candidate of Medical Sciences)

SO: Knizhnaya Letovis' No. 47, 19 November 1955. Moscow.

JEFIMENKO, V.L.

AVERBUKH, Ye.S.; YEFIMENKO, V.L.; IAPIROVA, M.H. (Leningred)

Disorders in the nervous activity in prolonged hyperinsulinism; adenoma of the isolands of Lengerhans. Klin.med. 35 [i.e.34] no.1 Supplement: 26-27 Ja '57. (MIRA 11:2)

1. Iz 3-go psikhiatricheskogo otdeleniya (nauchnyy rukovoditel' prof. Ye.S.Averbukh) Psikho-nevrologicheskogo hauchno-issledovatel'skogo instituta imeni V.M.Bekhtereva (dir. - prof. V.N.Myasishchev)
(NEFVOUS SYSTEM-DISEASES)
(PANCREAS-TUMORS)

Ude of reserpine in the treatment of hypertensive psychoses
[with summary in French]. Enuranevr. i psikh. 58 no.10:1190-1195 '58
(MIRA 11:11)

1. III psikhiatricheskaya klinika (rukovoditel' - prof. Ye. S.Averbukh)
Gosudarstvennogo nauchno-issledovatelskogo psikhonevrologicheskogo
instituta imeni V.M. Bekhtereva, Leningrad.
(HYPERTENSION, compl.
psychoses, reserpine ther. (Rus))
(PSYCHOSES, etiol. & pathogen.
hypertension, reserpine ther. (Rus))
(RESERPINE, ther. use.
psychoses caused by hypertensions (Rus))

#### YETIMENKO, V.L.

Use of chen-chiu therapy (acupuncture and moxa) in certain depressive syndromes; preliminary report. Zhur.nevr,i psikh. 59 no.10:1167-1171 (MIRA 13:3)

1. Leboratoriya igloterapii (nauchnyy rukovoditel' - prof. E.D. Tykochinskaya) i III psikhiatricheskaya klinika (nauchnyy rukovoditel' - prof. Ye.S. Averbukh) Nauchno-issledovatel'skogo psikhonevrologicheskogo instituta imeni V.M. Bekhtereva (direktor - prof. V.N. Myasishchev), Leniugrad.

(PSICHOSES MANIC DEPRESSIVE ther.)
(ACUFUNCTURE)
(MOXA)

AVERBUKH. Ye.S.; VISHNEVSKAYA, L.N.; GAPONOVA, V.D.; DOIL'NITSYNA, A.D.; YEFIMENKO, V.L.; LEBEDEV, B.A.

Modern approach to the investigation and treatment of mental disturbances in appertension. Trans Gos. nauch.—issl. psikhonevr. inst. no.20:149-162 '99.' (MIRA 14:1)

1. Gosudarstvennyy nauchno-isaledovatel skiy psikhonescologicheskiy institut imeni V.M. Bekhtereva, Leningrad.
(MENTAL ILLNESS) (HYPERTENSION)

#### YEFIMENKO, V.L.

Acupuncture therapy of some forms of psychoses and neuroses. Vop. psikh.i nevr. no.7:274-280 '61. (MIRA 15:8)

1. Iz laboratorii igloterapii (nauchnyy rukovoditel' - prof. E.D.Tykochinskaya) i III psikhiatricheskoy kliniki (nauchnyy rukovoditel' - prof. Ye.S.Averbukh) Nauchno-issledovatel'skogo psikhonevrologicheskogo instituta imeni V.M.Bekhtereva (dir. chlen-korrespondent Akademii pedagogicheskikh nauk RSFSR prof. V.N. Myasishchev).

(PSYCHOSES) (NEUROSES) (ACUPUNCTURE)

YEFIMENKO V.L.

Role of clinical psychopathological studies in the diagnosis of certain endocrine diseases. Trudy Gos. nauch.-issl. psikhonevr. inst. no.24: 181-187 '61. (MIRA 15:5)

1. 3-ye psikhiatricheskoye otdeleniye Gosudarstvennogo nauchno-issledo-vatel\*skogo psikhonevrologicheskogo instituta imeni V.M.Bekhtereva.

(ENDOCRINE GLANDS--DISEASES--DIAGNOSIS)

(PSYCHOLOGY, PATHOLOGICAL)

#### YEFIMENKO, V.L.

Treatment with tofranil of depressive states. Zhur. nevr. i psikh. 62 no.2:202-206 '62. (MIRA 15:6)

1. III psikhiatricheskaya klinika (nauchnyy rukovoditel: prof. Ye.S. Averbukh) Nauchno-issledovateliskogo psikhonevrologicheskogo instituta imeni V.M. Bekhtereva (dir. - kand.
med.nauk B.A. Lebedev), Leningrad.

(IMIPRAMINE)

(DEPRESSION, MENTAL)

# YEFIMENKO V.L.

Erythemic reaction of the skin to ultraviolet irradiation and its dynamics in the course of treatment in various forms of depression; reactivity of the autonomic nervous system in depressions. Zhur. nevr. i psikh. 63 no.10:1526-1531 163. (MIRA 17:5)

1. Fizicterapevticheskoye otdeleniye (nauchnyy rukovoditel:
prof. E.D. Tykochinskaya) i III psikhiatricheskaya klinika (nauchnyy
rukovoditel: - prof. Ye.S. Averbukh) Nauchno-issledovatel'skogo
instituta imeni V.M. Bekhtereva (dir. B.A. Lebedev), Leningrad.

YEFIMENCO, V.M.

Cadres for Soviet railroad transport and the system for training them. Zhel.dor.transp. 39 no.11:73-78 N '57. (MIRA 10:10)

1.Zamestitel' ministra putey soobshcheniya.

(Technical education)

 S/081/63/000/004/028/051 B149/B186

AUTHORS:

Gluzman, L. D., Leyba, V. S., Davidyan, D. N., Yefimenko, V. M.

TITLE:

The preparation of diphenic acid from phonanthrone

PERIODICAL:

Referativnyy zhurnal. Khimiya, no. 4, 1963, 461, abstract 4N78, (Sb. nauchn. tr. Ukr. n.-1. uglekhim, in-t.", no. 13 (35), 1962, 144 - 156)

TEXT: In order to develop an industrial method for the preparation of diphenic acid (I), a detailed study was made of liquid-phase exidation of both pure and commercial grade phenanthrene (II) with H<sub>2</sub>O<sub>2</sub> and CH<sub>3</sub>COOH (III). The reaction was performed under various conditions with successive alteration of the parameters affecting the course of the exidation: ratio of II, H<sub>2</sub>O<sub>2</sub> and III, concentrations of H<sub>2</sub>O<sub>2</sub> and III, temperature, duration of H<sub>2</sub>O<sub>2</sub> addition and duration of exidation, and intensity of stirring during the addition of H<sub>2</sub>O<sub>2</sub> and during auto-exidation. The effect of various catalysts (such as (NH<sub>4</sub>)<sub>2</sub>MoO<sub>4</sub>, MgSO<sub>4</sub>, MnSO<sub>4</sub>, CuSO<sub>4</sub>, KHSO<sub>4</sub>, CH<sub>3</sub>COONa, (CH<sub>3</sub>COO)<sub>2</sub>CO, V<sub>2</sub>O<sub>5</sub>, chrome-nickel alum and others), of different sorts of steel proposed Card 1/3

The preparation of diphenic acid ...

S/081/63/000/004/028/051 B149/B186

for the construction of the pilot plant [1X16H9T (1Kh18N9T) and 1X16H12M9T (1Kh18N12M9T)], of the quality of the initial II and its admixtures were investigated. The optimum conditions were found to be: ratio (in parts by weight) II:III:H2O2 (30%) = 1:5:3.2, temperature 90-92°, duration of oxidation. The period of addition of H2O2 has no effect on the yield of I. Stirring during the addition of H2O2 and during the reactions must be slow. The reaction can be achieved without catalysts (the ones listed above have no positive effect) with a 75-80% yield of I. The presence of anthracene (10-20%) and carbazole (2-5%) admixtures in II has no appreciable effect on the yield and quality of I. Optimum conditions for the isolation of I were found. The most complete isolation and highest degree of purity was achieved by: distillation of III under vacuum at 75% to 1/3 of the volume and cooling of the residue to 15°. The crystals which separate are washed on the filter with 10% solution of III. The yield of I (with m.p. ~2280) is 65-68%. The solubility of I in III, H2O, CH3COCH3, dioxane, CH3OH, C2H5OH, C6H6 and xylene was determined over the range 20-90° (the results are given in the form of graphs. For organic solvents, I is least soluble in C6H6 at Card 2/3

The preparation of diphenic acid...

S/081/63/000/004/028/051
B149/B186

25° (10.16 g); the solubility is twice this in xylene. A method of regeneration of III has been developed. [Abstracter's note: Complete translation.]

GORELIKOV, N.I. (Novosibirsk); YEFIMENKO, V.V. (Novosibirsk);

KORSHEVER, I.I. (Novosibirsk)

Device for digital balancing with a nonuniform coding cycle.
Avtometriia no.3:51-57 '65. (MIRA 19:1)

1. Submitted Feb. 8, 1965.

YEFTMENKC, V.V. (Novomilirsk)

Interference resistance of binary-decimal codes. Avionatria no.2:
(MIFA 18:9)

ACCESSION NR: AP5021344

UR/0120/65/000/004/0127/0129 621.318.57

AUTHOR: Yefimenko, V. V.

TITLE: Electronic transistorized low voltage key


SOURCE: Pribory i tekhnika eksperimenta, no. 4, 1965, 127-129

TOPIC TAGS: transistorized circuit, current stabilization, switching circuit, voltage stabilization

ABSTRACT: During the commutation of signals from high amplification channels constant current conservation must be maintained. This is usually achieved by means of balance circuits or special complex electronic keys. The present article describes an electronic transistorized low voltage key shown in Fig. 1 of the Enclosure. The key is made of a two-stage RC amplifier in which the load of the first tube is AC shunted by the resistance of the open transistor. The method for the compensation of interferences due to the residual transistor parameters is also given. The frequency response of the key is determined basically by the transistor characteristics. Transient processes last some 10-15 msec. The device is used for the switching of the registration amplifier of control delay lines 1/3 Card

CIA-RDP86-00513R001962320015-2" APPROVED FOR RELEASE: 09/19/2001

	, included the or season or a section of the sectio	and the second s	A			)
L 00058-66 ACCESSION NR	: AP5021344				for the	
4	eneric drums whi	ch are incorporated	in speciali	zed machines	figures.	
/	t madnetic occur	0				
			11 SO AN 555	SR, Novosibii	:sk	
ASSOCIATION	f Automation and	d Electrometry, SO A	n sssr)			1
•		ENCL: 01	SUB CO	DE: EC		
SUBMITTED:	17Jun64		•			
NO REF SOV:	002	OTHER: 001				
NO KEP DOT.						
					•	
						•



#### CIA-RDP86-00513R001962320015-2 "APPROVED FOR RELEASE: 09/19/2001

EWT(d) L 38220-66

ACC NR: AP6015236

UR/0410/65/000/002/0063/0068 SOURCE CODE:

AUTHOR: Yefimenko, V. V. (Novosibirsk)

ORG: none

TITLE: The interference-free properties of binary-decimal codes (

SOURCE: Avtometriya, no. 2, 1965, 63-68

TOPIC TAGS: binary code, coding evaluation, digital system

ABSTRACT: The resistance of binary-decimal codes to additive pulse interferences of short duration was examined, inasmuch as the literature on the subject appears to be contradictory. A quantitative characteristic of interference-free properties of binary-decimal codes is suggested; it takes into account the degree of mismatch of coding results with respect to the real value of the measured magnitude, as well as the probability of occurrence of this mismatch. Interferences of two kinds were considered: first-order (directly affecting the measured input value), and second-order (acting upon individual components and producing malfunctions). If the effect of second--order interference upon the digital device is dominating as compared to first-order interference, then codes 4221, 5121, and 3321 are optimum with respect to criteria  $M[|\Delta|]$ ,  $M[\Delta]$ , and  $D[\Delta]$ , respectively. Orig. art. has: 6 formulas, 2 tables.


SUBM DATE: 050ct64/

ORIG REF:

08

UDC: 681.142+621.317.7

机制度器



O L 09944-67 ACC NR: AP6035863 digital-balance principle. The measured voltage id fed into the input of the converter, whose output is coupled through a decoder to a readout indicator. To increase the operating speed, the converter incorporates two two-position comparison units to whose outputs the measured voltage is fed through controlled reference signal sources. The controlling inputs of the reference signal sources and outputs of the two-positional comparions units and the decoder are mutually coupled through a logic circuit whose output is also the output of the converter. Orig. art. has: 1 figure. 5105 ATD PRESS: 17May65/ SUBM DATE: SUB CODE: 09/

AUTHOR: Yefimenko, V. V.  ORG: none  TITLE: Six-character binary-decimal codes with single error detection  SOURCE: Avtometriya, no. 5, 1965, 84-86  TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code  ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zoro and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.  Cord 1/2	I, 08868-67 EWT(d)/EWP(1) IJP(c) BB/GG
ORG: none  TITLE: Six-character binary-decimal codes with single error detection  SOURCE: Avtometriya, no. 5, 1965, 84-86  TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code  ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zero and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	ACC NR: AP6016324 (N) SOURCE CODE: UR/0410/65/000/005/0084/0086
TITLE: Six-character binary-decimal codes with single error detection  SOURCE: Avtometriya, no. 5, 1965, 84-86  TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code  ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zoro and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	AUTHOR: Yefimenko, V. V.
TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code  ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zoro and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	$\iota_{\mathcal{C}}$
TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code  ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zoro and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	TITLE: Six-character binary-decimal codes with single error detection
ABSTRACT: An effective method of eliminating single pulse interference or homeostatic failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zero and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	SOURCE: Avtometriya, no. 5, 1965, 84-86
failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zero and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.	TOPIC TAGS: electronic computer, computer coding, computer design, computer reliability, binary code, error correcting code
	failure is described. It involves the coding of the measured value in a six-character redundant binary-decimal code. The code is formed from conventional binary-decimal codes by adding two binary digits which do not carry any information with respect to the measured value but only check the correctness of the selected code combination. The method can be used in the numerical coding of an unknown measured value when no odd-even check can be performed. The check is performed by two decimal digits with weights zero and one; the index of an absence of an error is the combination 10 by two checking digits. Thus, if one increases the number of characters of a conventional binary-decimal code 5211, the code 521101 is the result. Using such a code, all homeostatic errors can be found, including some errors that have a multiplicity above unity.

hor	neostat	ic em	rors is	has the	ased si	nce '	the cl	necks	are c	. орег ютрте	ia, Zi is ud	addit	ional	pos	sibil	i-	, e 
tie or	es for diagra	the dens.	sign o	of comp	uters W	itn	error	COLIN	ec (10)	1. 01	-B.				J. I		
SUI	B CODE:	09/	SUBM	DATE:	10May6	5/	ORIG	REF:	COO/	ОТН	REF:	000					
										•				•			
									•								
			•		,		•										
	•		•			•				•							
				•				,		•							
														•			
			•				-								* *	•	
	•														1		
	ard 2/	2 egk				<del> </del>			· .								

L 08869-67 EWP(d)/EWP(1)IJP(c) DB/GG ACC NRI APGO16323 (N)SOURCE CODE: UR/0410/65/000/005/0050/0057 Yefimenko, V. V. (Novosibirsk) AUTHOR: 36 ORG: none

TITLE: The selection of a binary-decimal code for automatic computers with a trinary error detector/comparison circuit

SOURCE: Avtometriya, no. 5, 1965, 50-57

TOPIC TAGS: computer coding, error correcting code, computer reliability, computer design, binary code

ABSTRACT: A trinary error detector (or comparison circuit) is defined as a device which distinguishes between three states: whether the measured quantity (or value) is larger, smaller or (with an accuracy up to a certain constant \*c) equal to the known value (or quantity). Problems involving the selection of a binary-decimal code for a computer that uses such devices have not yet been described in the literature. The author examined a computer model where the trinary error detector is a system with a polarized relay as a threshold element. The author examined a k-decade computer with digital balancing which uses a trinary error detector circuit with a constant E = \* \* 6/2. It is desirable to perform the coding parallel, using two channels. Compared

WDC: 681.142.+621.317.7

13

**Card** 1/2

ACC	869 <b>-</b> 67 Nr. AP60									-			0
to co 13 fo	ding in	one ch	annel,	the g	ain in r	response	speed i	s 14%.	Orig.	art.	has:	5 tab	les,
UB C	ODE: 09	9/	SUBM	DATE:	07Hay65	01	RIG REF:	002		•			
			•	~•									
						•		•		•			
									-	•	•		
<b>.</b>			•			•	•	•				•	• •
Card	2/2 <sup>6</sup> 6	şk							•				

#### "APPROVED FOR RELEASE: 09/19/2001 CIA

#### CIA-RDP86-00513R001962320015-2

GG/BB/GD-2 <u>r</u> 39890⊶66 BWr(d)/BMr(1)IJP(c)ACC NR. 196017383 SOURCE CODE: UR/0410/65/000/003/0051/0057 AUTHOR: Gorelikov, N. I. (Novosibirsk); Yefimenko, V. V. (Novosibirsk); Korshever, I. I. (Novosibirsk) ORG: none Digital devices with positional balancing with an uneven coding cycle SOURCE: Avtometriya, no. 3, 1965, 51-57 TOPIC TAGS: shift register, ferrite, computer coding, binary code, digital system ABSTRACT: The article discusses questions related to the design of digital devices with positional balancing (using binary-decimal code) with the goal of increasing operating speed. The increased speed is achieved by the use of an uneven cycle of digital coding. An analysis is made of devices for controlling digital instruments which will allow the simplest realization of this coding principle. Recommendations are given for the selection of a binary-decimal code for this type of devices, and the possibility of designing decades with variable code structure is investigated. The most suitable circuit for a control device is one based on single-cycle ferrite diode shift register or a sequential trigger distributor with one of the following codes used in all decades save the highest-order: 4221, 5211, 5311. The highest-order decade should be built with variable code structure, resulting in some increase in complexity but a considerable reduction in the number of comparisons required per decade. Orig. art. has: 1 table and 2 figures. [JPRS] SUB CODE: 09 / SUBM DATE: O8Feb65 / ORIG REF: 003 UDC: 621.317.7.083.5

#### "APPROVED FOR RELEASE: 09/19/2001 C

CIA-RDP86-00513R001962320015-2

YEFIMYENKO, Ye. I

29503

Pokae Na topografichyeskoy Kartye Masshtata. 1: 100 000 Elyemyentov Ryel'yefa, Nye Vyrazhayushchikhsya Gorisontalyami. Truby Tsyentr. Nauch-isslyed. in-ta Gyedyeeii, Aeros"yemki l Kartografii, vyp. 55, 1949, s. 29-34.

SO: Letopis' No. 40

YEFIMENKO, YEFIMENKO, Ye.I., kand.tekhn.nauk Representation of relief on general geographic maps. Trudy TSNIIGAIK no.92:105-154 '53. (MIRA (MIRA 10:12) (Relief maps)

CIA-RDP86-00513R001962320015-2"

स्म महाव<u>ुक्त</u>

**APPROVED FOR RELEASE: 09/19/2001** 

YEFIMENKO, Ye. 1

PHASE I BOOK EXPLOITATION

SOV/2266

Tsentral'nyy nauchno-issledovatel'skiy institut geodezii, aeros"yemki i kartografii.

Issledovaniya po kartografii (Studies in Cartography) [Moscow] Geodezizdat, 1958. 34 p. (Series: Its: Trudy, vyp. 126) Errata slip inserted. 1,500 copies

Spondoring Agency: Glavnoye upravleniye geodezii i kartografii MVD SSSR.

Ed.: Yu.G. Kel'ner; Ed. of Publishing House: T.A. Shamarova; Tech. Ed.: V.V.

PURPOSE: This issue of the Institute's Transactions is intended for cartographers

COVERAGE: This work is devoted to the study of two topics in cartography, topographic symbols and generalization. Maps, diagrams and photos accompany each article.

Lozinova, V.M. [Candidate of Technical Sciences] Improvement of the 1:100,000 card 1/2

CIA-RDP86-00513R001962320015-2" APPROVED FOR RELEASE: 09/19/2001

Studies in Cartography

sov/2266

Scale Maps
This article treats in detail methods recommended for improving the format, contents, and standard symbols of the 1: 100 000 scale series which gives complete and uniform coverage of the Soviet Union. Each map detail is discussed separately, i.e., roads, railroads, drainage, etc. with specific recommendations for improvement. Among the changes proposed are

cific recommendations for improvement. Among the changes proposed are better use of colors, especially for city plans and the elimination of ticks in railroad portrayal to make engraving easier. Proposed standard symbols are given in color as are sample map cut-outs. The samples given are of nonexistent areas. There are 35 references: 27 Soviet and 8 German.

Yefimenko, Ye.I. [Candidate of Technical Sciences] Examples of Generalization
In Reducing Maps From 1:10,000 to 1: 25,000 Scale
In this study the author describes some experimental compilations of
1: 25,000 scale maps based on 1: 1,000 scale source materials. Several
illustrations in the back of the text show sample terrain and town plans
at 1:25,000 scale after a direct reduction and after various methods of

selective compilation. There are 9 references, all Soviet.

AVAILABLE: Library of Congress

Card 2/2

MM/sfm 9-15-59

3

REL'NER, Yu.G.; YEFIMENKO, Ye.I.

Project of an Atlas of Antarctica. Geod. i kart. no.8:55-58
(MIRA 16:9)

Ag '63.

(Antarctica-Maps)

KOSSOVSKIY, Georgiy Nikolayevich, kand. tekhn. nauk; STRIZHEVSKIY, Mikhail Petrovich, tekhnik; YEFIMENKO, Yuriy Ivanovich, inzh.; SPYNU, G.A., kand. tekhn.nauk, Fevenzent, STEPANOVA, E.A., inzh., red. izd-va; BEREZOVYY, V.N., tekhn. red.

[The Ukrainian Scientific Research Institute of Mechanical Woodworking automatic line no.3 with programmed control of the setting of machines] Avtomaticheskaia linia UkrNIIMOD-3, s programmnym upravleniem nastroikoi stankov. Kiev, Gostekhizdat USSR, 1963. 21 p. (MIRA 16:9) (Woodworking machinery) (Automatic control)

507/6-58-7-3/13

AUTHORS:

Sokolova, N. A., Candidate of Technical Sciences, Yefizerko, Ye. I., Candidate of Technical Sciences,

Vanin, A. G.

TITLU:

A Stereotopographical Experimental Survey of an Alpine Region on a Scale of 1:25 000 (Opythaya rabota po stereotopograficheskoy s"yamke vysokogornogo uchastka v masshtabe 1:25 000)

PERIODICAL:

Geodeziya i kartografiya, 1958, Nr 7, pp. 14-26 (USSR)

ABSTRACT:

An experimental survey of an alpine region on a scale of 1:25 000 was carried out at the stereoprojector SPR-2 of the Taniigaik (Central Scientific Research Institute of Surveying, Aerial Photography and Cartography). The purpose of this work was to determine the scope of application of this apparatus and to work out suggestions for a representation of mountainous territory. Research pushed in this direction has not yet been concluded. This is a presentation of the results. The area and the sources for surveying are described. The section to be mapped is a typical alpine region with elevations reaching 4 000 m. The area covered by

Card 1/3

807/6-58-7-3/19

A Stereotopographical Experimental Survey of an Alpine Region on a Scale of 1:25 000

the survey was 100 km<sup>2</sup>. The cerial photographs were taken on a scale of 1: 40 000 with the aerial camera TE with a focal length of  $f_{t_0} = 100$ mm, an end overlap of 7c-85% and a side overlap of 40-70 %. The whole area of the section was covered by twelve aerial photographs, 232 control points were established. The second passage describes the storeophotogrammetric work and their succession. Some particular features in the orienting of aerial photographs of alpine territory of the work with the SPR-2 are mentioned. The deterination of the coordinates of points in the terrain and the estimation of the accuracy is mentioned. This equipment guarantees the required accuracy. In a table the accuracy of this and of other apparatus is compared. The surveying of soil elevations and of the contours is described and some practical suggestions are made. The third passage deals with the presentation of the elements of alpine territory in the original plotting map. Shortcomings occurring in the presentation are indicated. It is shown that a correct and accurate presentation is less dependent on the elevation in the cross-section than upon the technique of conducting

Card 2/3

store of the property of the p

1. Geology 2. Geophysical surveying 3. Aerial photography

Ocrd 3/3

oviet.

YEFIMENKO, Ye.I.; PROKHVATILOV, A.Ya.

Advanced work methods to be made available to every worker. Khim.volok. no.2:61-63 '63. (MIRA 16:5)

1. Kamenskiy kombinat iskusstvennogo volokna.

(Textile workers—Education and training)

MOSSOVSKIY, G.N., kand. tekhn. nauk; YEFIMENKO, Yu.I.

Feed bin for feeding blanks to automatic production lines.
Der. prom. 8 no.9:11 S '59. (MIRA 12:12)

1.Ukrainskiy nauchno-issledovatel'skiy institut mekhanicheskoy obrabotki drevesiny.

(Woodworking machinery)

L 11:39-66 EWT(m)/EPF(c)/EMP(N)/EMA(d)/T/EMP(t)/EMP(z)/EMP(b)/ETC(m) MJW/JD/WW/MB

ACCESSION NR: AP5022405 UR/0369/65/000/004/0477/0480

AUTHOR: Yefimenko, Yu. M.; Kuslitskiy, A. B.; Chaban, D. V.; Karpenko, G. V.;
Movohan, B. A. W.; Marting on properties of the ShKh15 bell
bearing steel (pH,5)

SOURCE: Fiziko-khimicheskaya mekhanika materialov, no. 4, 1965, 477-480

TOPIC TAGS: electron beam, ball bearing meeting on mechanical properties of the ShKh15 bail bearing steel was studied in order to compare the effectiveness of this technique with the effectiveness of the vacuum and slag smelting techniques of the electron beam smelting was conducted in a U-143 unit under 5:10 mm Hg.
As a result of this smelting treatment the oxygen/content dropped from 0.004 to 0.0007\$, nitrogen from 0.007 to 0.0013\$, hydrogen from 0.0001 to 0.0004\$, SiO2
from 0.0000 to 0.0004\$, Al203 from 0.0270 to 0.0018\$, FeO from 0.0007 to 0.0001\$, and CaO from 0.0005 to 0.0001\$. Electron beam smelted steel improved: resistance to cyclic deformation, corrosion resistance, and fatigue limit (33\$ increase).

L 11:39-66

ACCESSION NR: AP5022405

The mechanical strength of ShKhl5 steel ( $\sigma$  in kg/mm<sup>2</sup>) as a function of frequency of cyclic deformation (in millions of cycles) N, is shown in fig. 1 of the Enclosure. The corrosion resistance of ShKhl5 steel in 53%  $H_2SO_4$  solution is shown in fig. 2 of the Enclosure. Orig. art. has: 3 figures, 5 tables.

ASSOCIATION: Institut electrosyarki im. Ye. O. Patona, AN UkrSSR, Kiev (Institute of Electric Welding, AN UkrSSR)! Fiziko-mekhanicheskiy institut, AN UkrSSR, L'vov (Physico-Mechanical Institute, AN UkrSSR)

SUBMITTED: 24Mar65


ENCL: 02


SUB CODE: MM

NO REF SOV: 004

other: 000

Card 2/4





(//)
L 12183-66 EWT(m)/EWA(d)/EWP(t)/EWP(z)/EWP(b) MJW/JD

ACC NR: AP5028376 SOURCE CODE: UR/0369/65/001/005/0583/0587

AUTHOR: Kuslitskiy, A. B.; Kachmar, B. F.; Yefimenko, Yu. M.; Chaban, D. V. 57

ORG: Physics-engineering Institute, AN UkrSSR, L'vov (Fiziko-mekhanicheskiy B

ORG: Physics-engineering Institute, AN UkrSSR, L'vov (Fiziko-mekhanicheskiy institut AN UkrSSR); Electric Welding Institute im. Ye. O. Paton, AN UkrSSR, Kiev (Institut elektrosvarki AN UkrSSR)

TITLE: The effect of nonmetallic inclusions on the strength of hardened ShKh15 steel during hydrogenation

SOURCE: Fiziko-khimicheskaya mekhanika materialov, v. 1, no. 5, 1965, 583-587

TOPIC TAGS: steel property, hydrogenation, metal strength, nonmetallic inclusion, martensite steel, ball bearing steel, SOLID MECHANICAL PROPERTY

ABSTRACT: The authors determined the effect of impurities in martensite (HRC = 61-63) ball bearing steel on its mechanical properties during hydrogenation. The hydrogenation process sharply reduces the strength of steel of all methods of preparation, depending on the impurity content in the steel. An increase in the quantity of nonmetallic inclusions decreases the strength of the steel. The existing methods of qualitative and quantitative analyses of the content of nonmetallic inclusions (metallographic and electrolytic separation) do not provide Card 1/2

L 12183-66

ACC NR: AP5028376

sufficient reliability in the investigation of the higher grades of steel made by vacuum, molten slag electric process, and the electron-beam remelting methods. The most unfavorable nonmetallic inclusions are brittle particles, such as minute titanium inclusions and silica particles, which are not detectable by metallographic analysis. The most effective method of removing the nonmetallic inclusions and gases from the steel is the electron-beam remelting process. Orig. art. has: 2 figures and 3 tables.

SUB CODE: 11 / SUBM DATE: 11Apr65 / ORIG REF: 009 / OTH REF: 004

Card 2/2)

JD/DJ IJP(c) EWI(m)/EWA(d)/I/EWP(t) UR/0133/66/000/003/0230/0232 SOURCE CODE: AP6010134 Yefimenko, Yu. M.; Movchan, B. A.; Tikhonovskiy, A. L. AUTHOR: ORG: Electric Welding Institute im. Ye. O. Patona, AN UkrSSR (Institut elektrosvarki AN UkrSSR) TITLE: Electron-beam melting and purification of ShKh15 ball-bearing steel SOURCE: Stal', no. 3, 1966, 230-323 TOPIC TAGS: ball bearing steel, steel purification, steel melting, electron beam melting / Sakking ABSTRACT: Arc-melted ShKh15 ball-bearing steel was remelted in L-2 or U-143 electron-beam furnaces into 25-30 kg ingots with a diameter of 100 mm. The macrostructure of the ingots was dense and uniform; the shrinkage cavity extended to a depth of 0.2-0.3 diameter. Single or double remelting did not affect the carbon, silicon, and phosphorus contents but lowered the manganese, chromium, sulfur, oxygen, nitrogen, and hydrogen contents. After single remelting, manganese was reduced from 0.28 to 0.03-0.04%, chromium from 1.50 to 1.40-1.41%, sulfur from 0.015 to 0.006-0.008%, oxygen from 0.0040 to 0.0007-0.0010% nitrogen from 0.0070 to 0.0011-0.0013%, and hydrogen from 0.00010 669.187.26:621 Card 1/2

I. 2(6)0-66 ACC NR: AP6010134			
to 0.00001-0.00004%. Douexcept for the case of sultron-beam melting increase and reduced considerably to segregation was observed. the most rigid specifications and completely dispecifications.	ible remelting had no signiful fur; whose content dropped to the steel density from 7. The content of harmful incluons. The oxides and silicate steel hardenability was pite of the almost complete 4 figures.	811 to 7.822 g/cm <sup>3</sup> sions. No carbide inclusions met	3
SUB CODE: 11/ SUBM DATE:	none/ ORIG REF: 003/	[ww] ATD PRESS: 4225	
		•	
		i	

#### YEFIMENKO, Z. F.:

YEFIMENKO, Z. F.: "Methods of developing skill among Soviet readers through teaching". Leningrad, 1955. Leningrad State Pedagogical Inst imeni A. I. Gertsen, Chair of Pedagogy. (Dissertations for the Degree of Candidate of Pedagogical Sciences.)

So. Knizhnaya letopis'. No. 49, 3 December 1955. Moscow.

# YEFIMENKO, Z.F.

The teachers's mastery. Uch.zap.Len.un. no.214:171-184 '56.
(MIRA 10:3)
(Teaching)

YEFIMENKOVA, A. I., Cand of Chem Sci -- (diss) "Study or the Autooxidation of Decalin in a Liquid Phase," Mos, 1959, 12 pp (Moscow Chemival Technological Institute im D. I. Mendeleyev) (KL, 1-60, 120)

5 (1,3) LUTHORS:

sov/20-126-1-24/62 Kamneva, A. I., Fioshin, M. Ya.,

Yefimenkova, A. I., Vasil'yev, Yu. B.,

Muzychenko, L. A.

Investigation of the Process of Electrochemical Condensation Adipic Acid (Izucheniye TITLE:

protsessa elektrokhimicheskoy kondensatsii mono-2-etilgeksilo-

vogo efira adipinovoy kisloty)

PERIODICAL:

Doklady Akademii nauk SSSR, 1959, Vol 126, Nr 1, pp 90 - 92

(USSR)

The demand for high-molecular dicarboxylic acids and their ABSTRACT:

esters rose. The process mentioned in the title is therefore theoretically as well as practically interesting. It proceeds on the anode in the case of the electrolysis of the monoester--salt-solution in the aqueous and nonaqueous electrolyte (Ref 1). The authors obtained in this investigation for the first time the sebacic acid-di-2-ethyl-hexyl-ester by electrosynthesis which is used as the main component of high-quality lubricants. Nonaqueous electrolytes are scarcely suitable for the mentioned purpose. The authors used therefore an aqueous elec-

trolyte of the following composition: 300-400 g/l of the ester

Card 1/3

CIA-RDP86-00513R001962320015-2"

**APPROVED FOR RELEASE: 09/19/2001** 

Investigation of the Process of Electrochemical Condensation of the Mono-2-ethyl-hexyl-ester of Adipic Acid

507/20-126-1-24/62

mentioned in the title, 30-50 g/l K<sub>2</sub>CO<sub>3</sub> and 600-700 ml/water. Anode and cathode were of platinum. No diaphragm was used. Temperature 20-30°. The current density fluctuated at the anode between 10 and 60 a/dm². The yield of the main product: the sebacic acid-di-2-ethyl-hexyl-ester did not change with the current density. It amounted to 55% of the theoretical one. An intensive foam formation reduces the electrolyte considerably. This was eliminated by the isolating extraction with diethyl-ether. Finally the processes possible on the anode are discussed by means of the reactions (1) - (10). The hydrogen-superoxide theory of the electrosynthesis of Kolbe which was developed in most recent time by Glesstone (Ref 5) was in this case not confirmed (in line with Ref 6). Although the electrochemical condensation of the monoesters of dicarboxylic acids is to a certain extent similar to the electrosynthesis of Kolbe, the first mentioned one is a much more complicated process. The rules which govern the most simple case of an electrolysis of

Card 2/3

 Investigation of the Process of Electrochemical Condensation of the Mono-2-ethyl-hexyl-ester of Adipic Acid

507/20-126-1-24/62

the monobasic carboxylic acids must therefore not hold in the case of the first mentioned process. There are 6 references, 1 of which is Soviet.

ASSOCIATION:

Moskovskiy khimiko-tekhnologicheskiy institut im. D. I. Mendeleyeva (Moscow Institute of Chemical Technology imeni D. I. Mendeleyev)

PRESENTED:

February 21, 1959, by A. N. Frumkin, Academician

SUBMITTED:

February 17, 1959

Card 3/3

YEFIMETS, Ivan Dmitriyevich

[Electric power supply sources for communication apparatus] Istochniki elektropitaniia ustanovok svinzt. Leningrad, Leningrad, Leningrad, Leningrad, elektrotekhn. In-t svinzi im. M.A.Bonch-Bruevicha, No.2.[Use of storage batteries. Technical characteristics of charging and power supplying stations] Ekspluatatsiia akkumuliatorov. Tekhnicheskaia kancakteristika zariadnykh i elektropitaiushchikh stantsii; uchebnoe posobie. 1963. 49 p. (NIRA 17:7)

The second of the Arms of the	იოსად <del>ნ</del> ე ინე და აქანადებან. გა
ACTHOR: Pement'yeva, M. I.; Naumova, T. I.,	Yefimenkova, I. M.
Trought on the same of the contract of the con	The partition of the second
المانية المائية	
1	
70PIC TAGS: aromatic hydrocarbon, chromatog	grapny, chromatographic analysis
ABSTRACT: The products of catalytic reform	
consist of paraffin, napthene, and aromatic	
analyzed through pas-liquid chromatography.	
o acompleta o registra in construction of the interese and in the con-	
to at the transfer of the property of the transfer of the property of the transfer of the tran	en with the first of the first end of the second of the se
aromatic hydrocarbons on silica gel and ther	
arighy the extens of glycol and succinic of	
ा । विकास करा विकास करा है । विकास स्थापन करा स्थापन करा है	
the transfer of the section of the s	estems of the grant structure with the
Card 100	
Card 1/2	

ASSOCIATION: Whilestexing  Comparing the Com	୍ୟୀଞ୍ଚମ କର୍ମ NCCESSION NR: AP5006824		
Abbuciation: Antimettekning  comparing the contraction of the contract	page ty jo kambos pandu †s 	The mother from the same and	
NO FEET COVER COVE	cilinatitien – do	ince. A	Time Course Frig W
	NO ERF SOVE TOPO	OTHER: 100	

YEFIMETS, N.D.; GAL'CHINSKAYA, V.V., tekhn. red.

[Electric power supply sources of telecommunication systems]
Istochniki elektropitaniia ustanovok sviazi. Leningrad,
Leningr. elektro-tekhn. in-t sviazi im. M.A. Bonch-Bruevicha.
No.1.[Chemical sources of electric current]Khimicheskie istochniki toka; uchebnoe posobie. 1962. 77 p. (MIRA 16:1)

(Electric power supply to apparatus)

(Electric batteries)

YEFIMISHIN, N.S., kandidat meditsinskikh nauk.

Mechanism and diagnosis of subcutaneous traumatic ruptures of the spleen. Khirurgiia no.11:57-60 N '53. (MLRA 6:12)

1. Iz L'vovskogo nauchno-issledovatel'skogo instituta perelivaniya krovi i neotloshnoy khirurgii (direktor - dotsent D.G.Petrov, zamestitel' direktora po nauchnoy chasti - professor I.I.Fedorov).

(Spleen)

# 

#### YEFINISHIN, N.S., kand.med.nauk


Significance of exercise therapy in treating fractures of the pelvis. Ortop.travm. i protez. 19 no.5:85-87 S-0 '58 (MIRA 11:12)

1. Iz kafedry fakulitetskoy khirurgii (zav. - prof. E.A. Sakfelid)
Stanislavskogo meditsinskogo instituta.

(PELVIS, fract.

exercise ther. (Rus))

(EXERCISE, THERAPT in various dis.
pelvis fract. (Rus))



1. 15

YEFIMISHIN, N.S., kand. med. nauk.

Some problems of intra-arterial blood transfusion in severe shock: clinical experimental study. Khirurgiia, Mosk va 34 no.11:19-23 N '58.

(MIRA 12:1)

1. Iz fakul'tetskoy khirurgicheskoy kliniki (Zav. - prof. B.A. Sakfel'd) Stanislavskogo meditsinskogo instituta (dir. - dots. G.A. Babenko). (BLOOD TRANSFUSION

intra-arterial, in severe shock in human & animal subjects (Rus))

(SHOCK, ther.

blood transfusion, intra-arterial, in severe shock in human & animal subjects (Rus))

SAKFFLID, E.A., prof.; YEFIMISHIN, N.S., kand. med. nauk.

Surgical treatment of acute blood loss from the esophageal vein in portal hypertention. Khirurgiia, Moskva 34 no.11:41-45 N '58. (MIRA 12:1)

1. Iz fakul'tetskoy khirurgicheskoy kliniki (zav. - prof. E.A. Sakfel'd)
Stanislavskogo meditsinskogo instituta (dir. - dots. G.A. Babenko).

(HYPERTENSION, PORTAL, compl.

hemorrh. from esophageal varices, surg. (Rus))

#### YEFINISHIN, N.S.

Arterial blood transfusion in the light of an analysis of unsuccessful outcome [with summary in English, p.62]. Problegemat. 1 perel. krovi 4 no.1:37-40 Ja-F '59. (MIRA 12:2)

1. Iz kafedry fakul'tetskoy khirurgii (zav. - prof. E.A. Sakfel'd)
Stanislvaskogo meditsinskogo instituta.
(BLOOD PRESSURE,
intra-arterial, failure (Rus))

YEFIMISHIN, N.S., kand. med. nauk

Ligation of the common hepatic artery and its periarterial denervation under experimental and clinical conditions.

(MIRA 17:9)

1. Kafedra gospital'noy khirurgii (zav.- prof. S.A. Verkhratskiy) Stanislavskogo meditsinskogo instituta.

## YEFIMISHIN, N.S., kand. med. nauk

Assessment of some methods of operative treatment of portal hypertension in liver cirrhosis. Vest. khir. 93 no.9:13-17 S '64. (MIRA 18:4)

1. Iz gospital'noy khirurgicheskoy kliniki (zav. - prof. S.A. Verkhratskiy) Ivano-Frankovskogo meditsinskogo instituta.

E. C. C. Compared to proceed a supervision of processors o		YEFINAK	/// V./.			
Concessed corrects a Septembrian approximate and Concessed		1-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
R. E. Same  Proporting produces configurations in processions of a parameters of parameters and			Constitutes our totale a description succession	Constrained settatel memberents bus tracted to a	• :	
Projections produces appropriate planeauron and recommendation of the Section of			CCCP.			
symmetric deliphonics galacteric Management and Provided Statements (18 page 2 values)  P. E. Sterm.  P. Ste		_		Liberghumungen tangubam beatened leneenteime		
Description of the Contential Mosting of the Section of Section 1 (1997)  Description present (1997)  P. E. Same.  P. E. Same.  C. S. Fyrmen  (I status deployed synt as rightly informs about process of motions.  A. S. Systems  (C 10 Ao 16 vacca)  B. A. Systems  Crystatus sames advirate talendares.  B. H. Sames  A. R. Sames  A. R. Sames  A. R. Sames  A. S. Systems			заумового оборудования различного напичения для	• • •		
Description of the content of the			P. E. Sures,	(с 18 да 22 честв)		
P. E. Survey G. h. Fyrrer G. h. Fyrrer G. h. Fyrrer G. h. C. for the contents.  Il sold (c. 10 Ao. 15 vaccos)  A. A. Systems Crystales assers aberiance transferration.  A. R. Sharer Ansatzypa asserses aberiance transferration.  A. R. Sarrer Ansatzypa asserses transferration.  A. R. Sarrer Ansatzypa asserses transferration.  A. F. Systems A. R. Sharer A. R. Share		/	Процессы издолжения в помитувания в видеконе в	Crimal newspaper represents a presurrent ment.	1	
(c) I served hospital symmetry and tryptify normal flatter product and the product of the first product of the fir		· /	•	ALE MOSTROP TODOSCAPED		
II subta (c 10 Ao 16 vecos)  B. A. Spranson C. R. Searres Asserting Asserting transparent and Monunceous Recognitions from their and their terms are the substance of the Searres Asserting and Monunceous Recognitions for department of the Searres and Searce and Se			С. В. Гургооч () автома внертуры бумы из структуру потейся	A. A. Cysponerel		
(c 10 Ao 16 vacce)  A. A. Systems  Gryssbase samps amount relemances.  A. H. Samon  Anapatype untimes transferre and Mountains  Anapatype untimes transferre and Mountains  Towards  20  Toport ordenisted for the Contessial Stating of the Salastific Statesland Society of  Badio Regimenting and Electrical Communications ins. A. S. Paper (YERES), Samon,  G-12 June. 1959			• •			
Crystates saveys actives transaction.  B. H. Saeren  Appropria material transactions has December to the Appropriate active of the Salestiffs Technological Society of Paris Inglanding and Heatrical Commitmentation in. A. S. Paper (VEREE), Honory, 8-12 June, 1959				Budos sensocarustante draves uneta ara coctuma	. •	· .
Anaparysa marines transposes and Mexicacure specifications are deplication and analysis of the Scientific Technological Society of Redio Regimenting and Ricetrical Communications in. A. S. Peper (VERES), Museum, 8-12 June, 1959				A. F. Syperia		
report embnitted for the Contesnial Meeting of the Scientific Technological Society of Redio Engineering and Electrical Communications in. A. S. Paper (VECEIX), Masser, 8-12 June. 1959		•	Алература цистины теленаемая для Мектовского	Коррания всимненой длегов и плетина теления- ников инфракциям про передоц интофильнов		
Bedio Regimenting and Electrical Communications In. A. S. Paper (YEEEE), Mason, 8-12 June, 1959			**	* *		
Bedio Regimenting and Electrical Communications In. A. S. Paper (YEEEE), Mason, 8-12 June, 1959	٠.			•	•	
6-12 7-00. 1959	İ .		report submitted for the Contennial Meeting of	the Scientific Technological Society of	•	
6-12 7-00. 1959		(-	Badia Bactemering and Ricetrical Communicati	ann in. A. S. Poper (YMCESI), Massow,	· -	
					ľ	
	1.	•				
					· •	
4,						
					4.	
		L				
			Ţ.			

YEFIMKIN, V. I., Cand of Tech Sci -- (diss) "Analysis of the Distortion of Color Separation Through the Transmittance of Light Information by the Method of Quadratural Modulation of Approaching Frequencies," Leningrad, 1959, 11 pp (Leningrad Electrical Engineering Institute of Communication im Bonch-Burevich) (KL, 1-60, 122)

#### YEFINKIN, V. I.

Selecting the equal signal reference chromaticity for color television systems. Tekh.kino i telev. 4 no.9:62-65 S '60.

(MIRA 13:9)

1. Leningradskiy elektrotekhnicheskiy institut svyazi im. M.A. Bonch-Bruyevicha. (Color television)

S/194/61/000/010/071/082 31842 D271/D301

6,6000

Yefimkin, V.I.

AUTHOR: TITLE:

Signal spectrum compression in the system of stereo-

color television

PERIODICAL:

Referativnyy zhurnal. Avtomatika i radioelektronika, no. 10, 1961, 20, abstract 10 Kl39 (Tr. nauchno-tekhn. konferentsii Leningr. elektrotekhn. in-ta

svyazi, no. 2, L., 1961, 31-37)

A system of compatible stereoscopic color television The picture for the left eye is transmitted monochromatically with a full bandwidth (6 mc/s). For the right eye color picture is transmitted with a bandwidth of 1.5 mc/s. Wide band luminance signals amplitude modulate the carrier, narrow band signals are transmitted on the sub-carrier. Narrow band luminance signals quadrature modulate the sub-carrier, color difference signals quadrature modulate the sub-carrier. nals amplitude modulate the sub-carrier on alternate lines. Cathode

Card 1/2

Signal spectrum compression...

318i<sub>1</sub>2 S/194/61/000/010/071/082 D271/D301

ray tubes type 53NK2B (53LK2B) and 53NK4U (53LK4Ts), semi-transparent mirror and polaroid spectacles are used for reproduction. As colors are received by one eye only, saturation is insufficient and its correction is necessary. The complexity of the synchronization of switching systems is pointed out. 6 figures. 3 references. Abstracter's note: Complete translation 7

Card 2/2

APPROVED FOR RELEASE: 09/19/2001 CIA-RDP86-00513R001962320015-2"

+

### YEFİMKIN, V.I.

Distortion in the reproduction of the color of signals transmitted through channels with limited band-pass. Elektrosviaz: 15 no.10: 31-39 0 '61. (MIM 14:10)

 AKSENTOV, Yu.V.; GOL'DIN, A.A.; DZHAKONIYA, V.Ye.; DUSHKEVICH, N.I.; YERGANZHIYEV, N.A.; YEFIMKIN, V.I.; LIPAY, I.N.; MINENKO, Yu.G.; ODNOL'KO, V.V.; PEREVEZENTSEV, L.T.; TARANETS, D.A.; SHMAYOV, P.V., prof.; KUKOLEVA, T.V., red.; BELYAYEVA, V.V., tekhn. red.

[Theory and practice of color television] Teoriia i praktika tsvetnogo televideniia. Moskva, Sovetskoe radio, 1962. 661 p. (MIRA 16:1)

(Color television)

#### YEFIMKIN, V. I.,

"Analysis of the Distortion of Color Reproduction in the Transimission of Colored Information by the Method of Quadrature Modulation of the Subcarrier Frequency." Dissertation for the Degree of Candidate of Sciences, Leningrad Electrotechnic Inst. of Communication im. M. A. Bonch-Bruyevich. Defense held on 24 December 1959.

The main problem of the investigation was to investigate the crossover distortion due to the nonlinearity of the phase-frequency characteristics of the color channels in a system with quadrature modulation of the subcarrier. Norms are determined and are reinforced by experiment for the permissible phase-frequency distortion. One of the methods of international exchange of television programs (at OIR and ICCR standards) is proposed, without recoding and changing the standards.

Izv Vysshikh ucheb. zabed MViSSO SSSR po razdelu Radiotekhnika, vol. 6, No. 1, 1963 p. 98-102 (original checked--Cand. of Sciences as in original.)

ي ښارنځ	<u> 28 (8.), 26</u>		-	المراد المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم المعالم	
ACC NRI	AT5022898	S	OURCE.CODE: 1	UR/2776/65/000/043/0	
AUTHOR: D	zneladze, Zh. I	; Yelimkin, V. I.;	Yasinskaya, Y	v. s. 44,57	3+1
ORG: Cent	ral Scientific F	lesearch Institute kiy institut chern	of Ferrous Met	tallurgy, Moscow (Tse	entral'-
TITLE: De	termination of c	optimum deformation alloy containing 0	conditions fo 45% zirconium	or sintered billets o	
SOURCE: M Sbornik tr	oscow. Tsentral udov, no. 43, 19	l'nyy nauchno-issle 965. Poroshkovaya	dovatel'akiy i metallurgiya (	institut chernoy meta (Powder metallurgy),	11urgii. 140-144
		nolybdenum alloy, z um, sintered molybd		onium containing allo	oy, sin-
TsSDM-1 mo cylindrica	lybdenum-base al 1 specimens 20 m	loy with 0.45% zir	conium have be 30 mm high wer	intered molybdenum an een investigated. Si re upset under a pnew	intered umatic
60, and 80 out cracks	%. <u>TsSDM</u> molybo, but TsSDM-1 all	lenum withstood def Loy upset with 80%	ormation at all reduction at 1	and a reduction of 20 11 temperatures teste 1000C had deep cracks e in reduction was of	ed with-
after upse creased.	tting at 1000C, In TsSDM-1 alloy	but after upsetting, the hardness beg	g at 1200C and an to drop on	d above, the hardness ly with upsetting at explained by the high	1400C
Card 1/2					
PATRICIA DE SPECIA DA TA		energia de la companione de la companion	CONTRACTOR OF THE REAL PROPERTY.		AL CHERT CONTENT

L 4076-66

ACC NR: AT5022898

crystallization temperature of TsSDM-1 alloy, 1300—1350C. To determine the effect of the temperature of deformation on mechanical properties, sintered billets were forged and elongated with one reheating after 50% reduction. It was found that the mechanical properties of both materials improve with increasing reduction and lower temperature in the last stages of forging. For instance, molybdenum forged in the 950—750C range (second forging) with a reduction of 85% had a strength of 70—75 kg/mm² and an elongation of 25—30%. The TsSDM alloy forged in the 1200—800C range with 85% reduction had a tensile strength of 80—90 kg/mm² and an elongation of 2h—26%. Thus, sintered billets should be deformed in two steps. The billets should first be heated to 1400C (TsSDM molybdenum) or 1500—1600C (TsSDM alloy) and deformed with a reduction of 40—50%. Then the billets should be reheated to 950C (TsSDM molybdenum) or 1200C (TsSDM-1 alloy) and finish forged. The temperature of final forging for molybdenum and TsSDM-1 alloy should not exceed 750 and 800C, respectively. TsSDM and TsSDM-1 sheets, 1 x 500 x 500 mm, were hot rolled in several steps from forged bars 25—30 mm thick, with the final step done at low temperatures, as indicated above.

Orig. art. has: 4 figures and 1 table.

SUB CODE: MM/ SUBM DATE: none/ ORIG REF: 001/ OTH REF: 001/ ATD PRESS:4/12 8

BVK

8/165/60/000/004/011/012 A104/A129

AUTHORS:

Godin, Yu.N., Shneyerson, M.B., Yefimkina, S.S., Polshkov, M.K.

TITLE:

Investigation of sloping structures of the Russian stage by the cor-

relation method of refracted waves

PERIODICAL:

Akademiya nauk Turkmenskoy SSR. Izvestiya. Seriya fiziko-tekhniches-

kikh, khimicheskikh i geologicheskikh nauk, no. 4, 1960, 81 - 84

TEXT: In spite of the satisfactory results achieved by the method of reflected waves, which helped to disclose a number of structures in the Russian stage, the problem of successful geophysical prospecting of sloping, i.e., potential oil and gas bearing structures has not been solved. In some areas available equipment and prospecting methods fail to ensure proper tracing of waves reflected from the boundary of Devon and carbonaceous stages. In view of this it has been decided to try the correlation method of refracted waves. After some attempts in 1945-46 and 1951 a new prospecting series was commenced by members of the Volgo-Ural skaya (Tuymazinskaya) geophysical expedition of the Vsesoyuznyy nauchno-issledovatel skiy institut geofizicheskikh metodov razvedki [VNIIGeofiziki] (All-Union Scientific Research Institute of Geophysical Prospecting Methods under the

Card 1/3

S/165/60/000/004/011/012 A104/A129

Investigation of sloping structures ...

supervision of Yu.N. Godin. It was established that primary waves from Devon and carbonaceous boundaries have stable kinetic and dynamic properties, extensive tracing ranges and are easily distinguishable even in areas where the recording of reflected waves was thwarted by interferences. So far, prospecting has been carried out in the following areas of the Volga-Ural Region: Orenburgskaya, Saratovskaya and Kuybishevskaya Oblast RSFSR, Bashkirskaya and Tatarskaya ASSR and northern areas of Kazakhskaya SSR. Standard NC(-60 (PSS-60) and CC-30/60 (SS-30/60) installations were used. Seismic waves were recorded at mid-frequency filtration with a maximum response of 30 - 35 c/s and a filtering band of 15-25 c/s. Basic profiles were oriented crosswise to the assumed expansion of rocks. To overcome the difficulties in the interpretation of the hodographs of reflected waves, a special correction method was worked out (Ref. 4: G.I. Ovanesov Poiski struktur v BASSR [Structure prospecting in BASSR], Geologiya nefti, no. 10, 1958). The method is based on simultaneous use of direct and reversed hodographs of deep waves corresponding to the refracted strata of Devon and carbon deposits and line to of the first refracted stratum. Mathematical analysis shows that this method enabled the location of structures with amplitudes of 50 m and above to be made. In some areas the study of refracted waves should be coupled with the recording of reflected waves and the method of individual seismic sounding is recommended

Card 2/3

S/165/60/000/004/011/012 A104/A129

Investigation of sloping structures ...

for this purpose. Conclusions: Prospecting by the correlation method of refracted waves carried out in the Bishidinskoye Upheaval, Serafimsko-Baltayevskiy terrace and Dimitrovskaya Structure was confirmed by drilling results. Exploration of virgin areas (Blizhneye Saratovskoye Zavol'zhe, Orenburgskaya Oblast') provided information on their tectonic formation and disclosed a number of anticlinal crests in the refracted strata. The described method opens new fields to seismic prospecting in south-eastern regions of the Russian stage. Satisfactory results were achieved in the TSSR and UzSSR. There are 2 figures and 6 Soviet-bloc references.

ASSOCIATION: VNIIGeofiziki

SUBMITTED: March 1, 1960

Card 3/3

BLOKHIN, P.A., GODIN, Yu.N.; YEFIMKINA, S.S., SHURSHEVA, T.I.

Searching for reefy massifs. Prikl. geofiz. no.28:10-22 '60.

(MIRA 14:3)

(Bashkiria—Seismic prospecting)

SHNEYERSON, M.B.; YEFIMKINA, S.S.

Some results of using the correlation refracted wave method in searching for dipping structures in the eastern Russian Platform. Prikl. geofiz. no.33:73-84 162. (MIRA 15:10) (Russian Platform—Seismic prospecting)

YEFIMKINA, S.S.; KOLENKOV, E.V.; SHNEYERSON, M.B.; SHTFYNBERG, G.G.

Methods of searching for structures of reef origin in the Orenburg part of the Ural Mountain region. Razved. geofiz. no.1:17-26 '64. (MIRA 18:7)

YEFIMKINA, V.F., inzh.

Meeting on the lighting of buildings having no windows or skylights. Svetotekhuika 6 no.8:30 Ag '60. (MIRA 13:11) (Electric lighting)

#### YEFIMKINA, V.F., inzh.

Fire hazard of fluorscent lighting fixtures. Syetotekhnika 6 no.10:24 0 160. (MIRA 13:9)

1. Vsesoyuznyy svetoteknicheskiy institut. (Fluorscent lamps)

#### S/196/61/000/009/015/052 E194/E155

AUTHORS: Ayzenberg, Yu.B., Bogolyubov, A.L., and Yefimkina, V.F.

TITLE: Dust and water protected fluorescent lamp fittings

PERIODICAL: Referativnyy zhurnal, Elektrotekhnika i energetika, no.9, 1961, 13-14, abstract 9V 113. (Svetotekhnika,

1961, no.1, 11-14)

TEXT: The fitting consists of a sheet-steel frame, reflector, diffuser and suspension arrangements. A symmetrical two-lamp start and control device is fixed inside the frame. The new small-sized lamp holders are used. The diffuser is made of transparent plastic and is firmly pressed to the frame by special clips; it is sealed with a lining of 'paralon'. For convenience whilst changing lamps and cleaning, the diffuser when open remains suspended on special chains. The fittings may either be installed in a long luminous line using a sealed main box or mounted individually on suspension rods. The conductors are brought in through glands. A description is also given of another dust- and water-proof fluorescent lamp fitting with an internal reflecting surface.

Card 1/1 [Abstractor's note: Complete translation.]